



MEB-100



MEB-400



MEB-500



XB-051

Crimping tool for insulated and non-insulated terminals.

For use with cable sections 1.5, 2.5 and 6mm2

Cuts and strips cable sections 0.75 to 6.0mm2

Cuts bolts up to M-5: Length: 225mm \$\infty\$\text{\$\infty}\$: 200g. \$\infty\$: 1



XB-051-J



XB-044

Crimps cable and cable insulation in one operation. Suitable for insulated terminal sections DIN: 1.5, 2.5 and 6mm2. AWG22 -16, 16-14, and 12-10. Cuts and strips cable sections 0.75 to 6mm. Length: 215mm. \bigcirc : 520g. \Longrightarrow : 1



MH-3-D

Crimps cable and cable insulation in one operation. Suitable for insulated terminal sections DIN: 1.5, 2.5 and 6mm2 AWG22 –16, 16-14, and 12-10.

Length: 240mm 🕰: 445g. 🖃: 1



MH-3-DM

Crimps cable and cable insulation in one operation. Suitable for insulated terminal sections DIN: 1.5, 2.5 and 6mm2. AWG22 -16, 16-14, and 12-10. Length: 240mm ◆ : 445g. ≥ : 1

DOUBLE CRIMP



AN-03-C

Ergonomic Handles, Ratchet tool with controlled calibration, Crimps cable and cable insulation in one operation. Suitable for insulated terminal sections DIN: 1.5, 2.5 and 6mm2. AWG22 -16, 16-14, and 12-10 Length: 230mm ◆◆: 600g. ₩: 1



LY-04-C

Crimps cable and cable insulation in one operation. Suitable for insulated terminal sections DIN: 1.5, 2.5 and 6mm2 AWG22 -16, 16-14, and 12-10

Length: 230mm →: 600g. →: 1



LY-03-C

Crimps cable and cable insulation in one operation. Suitable for insulated terminal sections DIN: 1.5, 2.5 and 6mm2. AWG22 -16, 16-14, and 12-10 Length: 230mm ◆◆: 600g. ►: 1





KH-13

Specially designed for crimping closed-end connectors NCE-1. NCE1-1.NCE-2. NCE-2-1 NCE-5. NCE-5-1 Cable sections in mm2: 0.5 -1.75, 1.0 - 3.0 and 2.5 - 6.0 Length: 270mm ◆◆: 600g. ₩: 1



MH-25

Specially designed for crimping closed-end connectors NCE-1. NCE-1-1. NCE-2. NCE-2-1. NCE-5. NCE-5-1. Cable sections in mm2: 0.5 - 1.75, 1.0 - 3.0 AND 2.5 - 6.0

Length: 265mm 45: 450g. 20: 1



MH-3-SB

Specially designed for crimping WATERPROOF (heat shrinkable tubing with polyamide adhesive) connectors. AWG 22-18, 18-16, 16-14, 12-10. UL: 0.3-0.5, 0.75-1.25, 2.0 and 5.5mm2

Length: 240mm ◆ 3425g. ►: 1